

ROTEX AUTOMATION LIMITED

Address : 987/11, GIDC Makarpura, Vadodara - 390 010, India.

Website : www.rotexautomation.com

E-mail : info@rotexautomation.com

*Engineering For The Future***DATASHEET**

Type of Valve	: 3/2 Direct acting Universal Valve
Ordering Code	: 30334-5-2R-B5-M6-S1+III-24V-DC-39-CO-SS-H-04
Item Code	:
Port Connection	: 1/4" NPT(F)
Orifice Size (mm)	: 5 mm
Flow Factor (kv)	: 8 LPM
Body Material	: Stainless Steel 316 with internal wetted parts of Stainless Steel 316
Manual Override	: Manual Override Provided Push to operate momentarily, for stayput using Screw Driver push & turn CW to operate valve
Seat Seal Material	: EPDM
Media	: Air, Water
Main Pressure	: 0 - 10 bar
Media Temp Range	: -50°C to +130°C
Type of Solenoid	: Flameproof Enclosure Ex d having integrated Terminals, Horizontal Cable Entry M20X1.5mm (F)
Size of Coil	: III
Enclosure Material	: Stainless Steel Cast CF8M
Special Version	: Surge Suppressor
Voltage	: 24V DC (-20%, +20%)
Power of Coil	: 8 W
Insulation Class	: Class H
Approval	: CuTR-EAC + ATEX
Coil Certificate nr.	: RU C-IN.AA71.B.00298/20
Marking	: 1 Ex db IIC T6/ T5/ T4 Gb Ex tb IIIC T80 °C/ 95 °C/ 130 °C Db, IP66 -40 °C ≤ Ta ≤ 35 °C FOR T6 -40 °C ≤ Ta ≤ 50 °C FOR T5 -40 °C ≤ Ta ≤ 60 °C FOR T4
Created By: Raj	Print Date And Time: 30/10/2023 19:38
This is System Generated Report	

Reg. Office : 987/11, GIDC, Makarpura, Vadodara – 390 010, India.

Jurisdiction : Vadodara, Gujarat, India.

CIN NO. : U29259GJ1983PLC005831 GST NO. : 24AABCR0011J1Z0

Phone : +91 265 617 4100

+91 265 263 8136

Fax : +91 265 263 1352