

ROTEX AUTOMATION LIMITED

Address : 987/11, GIDC Makarpura, Vadodara - 390 010, India.

Website : www.rotexautomation.com

E-mail : info@rotexautomation.com

*Engineering For The Future***DATASHEET**

Type of Valve	: 3/2 Direct acting Universal Valve
Ordering Code	: 30334-7-2R-B5-M6-S1+II-24V-DC-87-MS-LW15-H-04
Item Code	:
Port Connection	: 1/4" NPT(F)
Orifice Size (mm)	: 7 mm
Flow Factor (kv)	: 14 LPM
Body Material	: Stainless Steel 316 with internal wetted parts of Stainless Steel 316
Manual Override	: Manual Override Provided Push to operate momentarily, for stayput using Screw Driver push & turn CW to operate valve
Seat Seal Material	: EPDM
Media	: Air, Water
Main Pressure	: 0 - 10 bar
Media Temp Range	: -50°C to +130°C
Type of Solenoid	: Flameproof Enclosure Ex d having integrated Terminals, Bottom Cable Entry M20X1.5mm(F), IP67
Size of Coil	: II
Enclosure Material	: Aluminium Cast Powder coated
Voltage	: 24V DC (-20%, +20%)
Power of Coil	: 15 W
Insulation Class	: Class H
Approval	: CuTR-EAC + ATEX
Coil Certificate nr.	: RU C-IN.AA71.B.00298/20
Marking	: 1 Ex db IIC T5/ T4/ T3 Gb Ex tb IIIC T 95 °C / 130 °C / 195 °C Db, IP67 -60 °C ≤ Ta ≤ 45 °C for T5 -60 °C ≤ Ta ≤ 80 °C for T4 -60 °C ≤ Ta ≤ 100 °C for T3
Created By: Raj	Print Date And Time: 24/12/2023 00:29
This is System Generated Report	

Reg. Office : 987/11, GIDC, Makarpura, Vadodara – 390 010, India.

Jurisdiction : Vadodara, Gujarat, India.

CIN NO. : U29259GJ1983PLC005831 GST NO. : 24AABCR0011J1Z0

Phone : +91 265 617 4100

+91 265 263 8136

Fax : +91 265 263 1352