

ROTEX AUTOMATION LIMITED

Address : 987/11, GIDC Makarpura, Vadodara - 390 010, India.

Website : www.rotexautomation.comE-mail : info@rotexautomation.com*Engineering For The Future***DATASHEET**

Type of Valve	: 5/2 - 3/2 Convertible Internal Pilot Operated Single Solenoid Namur Valve
Ordering Code	: 51450V02-6-2R-S19+III-24V-DC-16-H
Item Code	:
Port Connection	: 1/4" NPT(F)
Orifice Size (mm)	: 6 mm
Flow Factor (kv)	: 12 LPM
Body Material	: Aluminium Hard Anodised
Manual Override	: Manual Override Provided Push to operate momentarily, for stayput using Screw Driver push & turn CW to operate valve
Seat Seal Material	: FLOUROSILICON
Media	: Air
Main Pressure	: 2 - 10 bar
Media Temp Range	: -60°C to +190°C
Type of Solenoid	: Weather Proof Enclosure having integral Terminals, Horizontal Cable Entry 1/2"NPT(F), IP67
Size of Coil	: III
Enclosure Material	: Aluminium Cast Epoxy Powder coated
Voltage	: 24V DC (-20%, +20%)
Power of Coil	: 8 W
Insulation Class	: Class H
Approval	: Weather proof
Coil Certificate nr.	: KLPL/BTG/18/01-10 FOR IP 67
Marking	: Weather Proof IP67
Created By: Raj	Print Date And Time: 24/07/2024 09:01
This is System Generated Report	

Reg. Office : 987/11, GIDC, Makarpura, Vadodara – 390 010, India.

Jurisdiction : Vadodara, Gujarat, India.

CIN NO. : U29259GJ1983PLC005831 GST NO. : 24AABCR0011J1Z0

Phone : +91 265 617 4100

+91 265 263 8136

Fax : +91 265 263 1352